

YO9-99-270
Amendment dated 4/7/2003

09/489,908

00280552aa
Reply to office action mailed 03/07/2003

The following is a complete listing of all claims in the application, with an indication of the status of each:

Listing of claims:

91 2117
1. (currently amended) A method for authenticating a user and for input of control information for an electronic device, said method comprising:
acquiring through a scanner at least two fingerprint images of a finger;
[and]
extracting from each said fingerprint image at least one contact parameter, calculated by computing correlations between image attributes in each said fingerprint image; and
using said fingerprint images and said at least one contact parameter to authenticate said user and to control said electronic device.

1 2. (original) A method as in claim 1, wherein said contact parameter is
2 rotation.

1 3. (original) A method as in claim 1, wherein said contact parameter is
2 translation.

1 4. (original) A method as in claim 3, further comprising calculating pitch and
2 roll rotations.

1 5. (original) A method as in claim 1, further comprising computing
2 correlations of a single portion of said image.

YO9-99-270
Amendment dated 4/7/2003

09/489,908

00280552aa
Reply to office action mailed 03/07/2003

1 6. (original) A method as in claim 1, further comprising computing
2 correlations between a multiplicity of small regions.

1 7. (original) A method as in claim 1 further comprising determining the rate
2 of change of some control parameter where a rotation or translation of said
3 finger relative to a reference position is used to determine the rate of change
4 of some control parameter of the computer.

1 8. (currently amended) A method as in claim 7 further comprising, measuring
2 a pitch and roll rotation, and using said rotation to control the position of a
3 cursor in the computer.

1 9. (original) A method as in claim 7 wherein said the reference position is the
2 position at which contact with the scanner is first registered, the reference
3 point being reset every time the finger reestablishes contact with the scanner.

1 10. (original) A method as in claim 1 further comprising comparing
2 successive, and possibly consecutive, images taken from a single period of
3 contact of said finger with said scanner.

1 11. (currently amended) A method as in claim 1 wherein at least one of said
2 fingerprint images is a reference image captured previously.

1 12. (original) A method as in claim 11 wherein the reference image is labeled
2 with known rotation information.

A1

YO9-99-270
Amendment dated 4/7/2003

09/489,908

00280552aa
Reply to office action mailed 03/07/2003

1 13. (original) A method as in claim 12 further comprising prompting the user
2 to present the finger at known rotations in an enrollment stage to provide said
3 known rotation information

1 14. (currently amended) A system for authenticating a user and for input of
2 pointing information for a computer, said system comprising:
3 a fingerprint image acquisition scanner for acquiring a fingerprint
4 image of a finger, wherein said scanner is able to capture successive images of
5 a finger in motion on a surface of said scanner; [and]

6 an image processor for extracting from said fingerprint image at least
7 one contact parameter other than any optional authentication status data for
8 said fingerprint image; and

9 means for using said successive fingerprint images and said at least
10 one contact parameter to control a pointing device and to authenticate said
11 user.

AI
1 15. (original) A system as in claim 14 wherein a multiplicity of variations in
2 each of said contact parameters are used to verify an acquisition of data in real
3 time from a live user.

1 16. (original) A system as in claim 15 wherein a user is directed by the
2 system to follow through on any combination of a multiplicity of prompts
3 including: change a position of, add pressure to contact or rotate said finger
4 from which a fingerprint image is acquired and wherein said multiplicity of
5 prompts are verified by the system to ensure that the data is being generated at
6 the time of direction.

YO9-99-270
Amendment dated 4/7/2003

09/489,908

00280552aa
Reply to office action mailed 03/07/2003

1 17. (original) A system as in claim 14 where the user is prompted to enact a
2 sequence of finger actions previously registered by the user as a "password"
3 for the device.

1 18. (original) A system as in claim 14 wherein a motion of the finger tip is
2 interpreted as a gesture for recognition by a gesture engine, for instance
3 character recognition or a Graffiti like engine.

1 19. (original) The system of claim 14, further comprising:
2 a feature extraction processor for extracting representative features
3 from said fingerprint image;
4 a memory for storing representative features of at least one authorized
5 user; and
6 a feature comparison processor for comparing said stored
7 representative features with said extracted representative features, and
8 generating authentication status data therefrom.

1 20. (original) A system as in claim 19 wherein an identity of a user is used to
2 set customized features of the computer.

1 21. (original) A system as in claim 19 where the identity of said user is used
2 to set customized parameters of the pointing device.

1 22. (currently amended) A system for imaging a fingerprint for input of
2 control information for an electronic device, said system comprising:
3 a fingerprint image acquisition scanner for acquiring a fingerprint
4 image of a finger, wherein said scanner is able to capture successive images of
5 a finger in motion on a surface of said scanner; and

A1

YO9-99-270
Amendment dated 4/7/2003

09/489,908

00280552aa
Reply to office action mailed 03/07/2003

6 an image processor for extracting from said finger print image at least
7 one contact parameter, representing the angle of the finger in relation to the
8 scanner, where said angle is calculated by computing correlations between
9 image attributes an two or more images acquired from scanners,
10 wherein said successive fingerprint images and said at least one
11 contact parameter are used for control of said electronic device and for
12 authentication of a user.

1 23. (currently amended) A system for authenticating a user and for input of
2 pointing information for a computer, said system comprising:

3 a multiplicity of fingerprint image acquisition scanners providing a
4 large input surface for acquiring [a fingerprint image] successive fingerprint
5 images of a finger; and

6 an image processor for extracting from each said fingerprint image at
7 least one contact parameter other than any optional authentication status data
8 for said fingerprint image; and

9 means for using said fingerprint images and said at least one contact
10 parameter to authenticate said user and as input of pointing information for a
11 computer.

1 24. (original) A system as in claim 23, where the scanner consists of a one-
2 dimensional array of small fingerprint scanners.

1 25. (original) A system as in claim 24, where the scanner consists of a two-
2 dimensional array of small fingerprint scanners.

YO9-99-270
Amendment dated 4/7/2003

09/489,908

00280552aa

Reply to office action mailed 03/07/2003

AI
1 26. (original) A system as in claim 17, where the "password" is a sequence of
2 touching individual small fingerprint scanners in a specific order with the
3 same finger. *by*
cont

1 27. (original) A system as in claim 26, where the password is a sequence or
2 touching individual small fingerprint scanners in a specific order, with more
3 than one finger being used in the sequence either serially or in parallel.
